



INDUSTRY 4.0

- Machine Built-in with OPC-UA interface

HIGHLIGHT PERFORMANCE

- Servo motor drive system
- Visual HMI operation interface
- 10.4 inch or larger touch screen
- Precision intelligence, closed loop monitoring, automatic proportional adjustment
- Very low noise, low energy, oil-free consumption
 - Suitable for dust-free workshops and high-end product production
 - Accept FDA standard orders

FUTURE ADVANTAGE


- Scalable future needs
- High-precision color metering device
- Or Other needs can be consulted

LSR

PGN



OPTIONS



TECHNICAL DATA

Viscosity	1,000,000 mPas
Output mixed material	800 g/min (depending on viscosity)
Mixing ratio	1:1 or variable
Color metering	0.3% ~ 4%
Actuation	Servo motor drive
Electric data	230-400 VAC, 50-60 Hz (3P+PE), 16A
Connection LIM machine	24V
Pneumatic system	R1/4", 6 bar low
Weight	760 kg
Dimensions	1,030 x 1,112 x 1,950 mm (W x D x H) (Height +800 mm if pump completely lifted)



2KM MUCOMAC Multi component special machinery (Guangzhou) Co., Ltd
Add: No. Sheng Li Industrial Park North of Chao tian industrial zone shi Lian Lu
Shi Lou Town Panyu Distri Guangzhou P.R.C Postcode: 511447

Tel: +8620 - 34852366 / 2866
Fax: +8620 - 34852966 / 2566
Email: info@2kmmucomac.com

www.2kmmucomac.com

www.mucomac.com

Service hotline

400-900-3889